BERTHON-JONES et al. Appl. No. 10/533,928

## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1.-18. (Cancelled)

 (Previously Presented) A mask assembly for application of non-invasive positive pressure ventilation to a patient, comprising:

a frame including a main body having at least one aperture configured to receive a supply of breathable gas under pressure, said frame including at least one selected frame portion provided to the main body, said at least one selected frame portion being adjustable relative to the main body; and

a cushion provided to the frame, the cushion being structured to provide an interface with the patient,

wherein said at least one selected frame portion is engaged with the cushion so that the cushion is adjustable in accordance with a position of said at least one selected frame portion relative to the main body, and

said cushion, upon application of positive pressure, applying a force to the patient, said force being adjustable in accordance with 1) the position of said at least one selected frame portion relative to the main body for a given value of said positive pressure; and/or 2) variations in the positive pressure.

BERTHON-JONES et al. Appl. No. 10/533,928

20. (Previously Presented) The mask assembly of claim 19, further comprising at

least one headgear connector portion provided to said at least one selected frame portion, said at

least one selected frame portion adapted to be movable in accordance with change in headgear

strap tension to thereby adjust the force applied to the sides of the patient's nose and/or face in

use.

21. (Previously Presented) The mask assembly of claim 19, wherein the frame

includes an adjustment mechanism including at least one and preferably a plurality of spaced

knobs operable to change the relative positioning between the main body and the at least one

selected frame portion.

22. (Previously Presented) The mask assembly of claim 19, wherein the at least one

selected frame portion includes a flexible member supporting the cushion.

23. (Previously Presented) The mask assembly of claim 19, wherein the main body

and the at least one selected frame portion are provided as two separate parts that are coupled to

one another.

24. (Previously Presented) The mask assembly of claim 19, wherein the main body

and the at least one selected frame portion are moveable by a camming mechanism.

-6-

1431425

BERTHON-JONES et al. Appl. No. 10/533,928

25. (Previously Presented) The mask assembly of claim 19, wherein the cushion

includes at least one inflatable element therein, adapted to adjust an effective stiffness and/or an

effective fit with the patient.

26. (Previously Presented) The mask assembly of claim 25, wherein the at least one

inflatable element is provided to selectively adjust a size of a nasal bridge region of the cushion.

27. (Previously Presented) The mask assembly of claim 19, wherein the at least one

selected frame portion includes each lateral side of the frame which is made of a flexible

material.

28. (Original) The mask assembly of claim 19, wherein the cushion includes at least

one element providing for multiple stiffening rates of the cushion upon changes in the force.

29.-33. (Cancelled)

34. (Previously Presented) A mask assembly for application of non-invasive positive

pressure ventilation to a patient, comprising:

a frame including a main body having at least one aperture configured to receive a supply

of breathable gas under pressure, said frame including a selected frame portion provided to the

main body, said selected frame portion being adjustable relative to the main body; and

a cushion provided to the frame, the cushion being structured to provide an interface with

the patient,

-7-

1431425

BERTHON-JONES et al. Appl. No. 10/533,928

wherein the selected frame portion is engaged with the cushion so that the cushion is

adjustable in accordance with a position of the selected frame portion relative to the main body,

and

wherein the selected frame portion includes each lateral side of the frame, and the

selected frame portion is bendable to cause each lateral side of the frame to push against sides of

the cushion.

35. (Previously Presented) The mask assembly of claim 34, wherein the selected

frame portion includes a flexible member supporting the cushion.

36. (Previously Presented) The mask assembly of claim 35, wherein the main body is

relatively stiffer than the flexible member.

37. (Previously Presented) The mask assembly of claim 34, wherein the main body

and the selected frame portion are provided as two separate parts that are coupled to one another.

38. (Previously Presented) The mask assembly of claim 34, wherein the selected

frame portion includes each lateral side of the frame which is made of a flexible material.

39. (Previously Presented) The mask assembly of claim 34, wherein the selected

frame portion is bendable about a longitudinal axis of the frame.

- 8 -

1431425

BERTHON-JONES et al. Appl. No. 10/533,928

40. (Previously Presented) The mask assembly of claim 34, wherein the selected

frame portion includes side wing portions which are movable relative to the main body to adjust

the sides of the cushion.

41. (Previously Presented) The mask assembly of claim 40, wherein each of the side

wing portions are adjustable into a plurality of positions.

42. (Previously Presented) The mask assembly of claim 34, wherein the cushion is

adapted to provide a seal with the patient's nose.

43. (Previously Presented) The mask assembly of claim 19, wherein said at least one

selected frame portion is adjustable to deform the cushion to adjust the fit and/or seal of the

cushion on the patient's face.

44. (Previously Presented) The mask assembly of claim 34, wherein the selected

frame portion is adjustable to deform the cushion to adjust the fit and/or seal of the cushion on

the patient's face.